

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : <b>D21F 5/04</b>		<b>A1</b>	(11) International Publication Number: <b>WO 00/50692</b>
			(43) International Publication Date: 31 August 2000 (31.08.00)
(21) International Application Number: PCT/FI00/00129		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 21 February 2000 (21.02.00)			
(30) Priority Data: 990370 22 February 1999 (22.02.99) FI 19991908 8 September 1999 (08.09.99) FI			
(71) Applicant (for all designated States except US): VALMET CORPORATION [FI/FI]; Fabianinkatu 9 A, FIN-00130 Helsinki (FI).			
(72) Inventors; and (75) Inventors/Applicants (for US only): JOKINEN, Reijo [FI/FI]; Kriivarinkuja 3, FIN-21280 Raisio (FI). KOMULAINEN, Antti [FI/FI]; Tarhiantie 22, FIN-42700 Keuruu (FI). JUPPI, Kari [FI/FI]; Hiekkapohjantie 259, FIN-40270 Palokka (FI).			
(74) Agent: TURUN PATENTTITOIMISTO OY; P.O. Box 99, FIN-20521 Turku (FI).		<p><b>Published</b></p> <p>With international search report.</p> <p>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p> <p>In English translation (filed in Finnish).</p>	

(54) Title: METHOD AND APPARATUS IN THE DRYING SECTION OF A PAPER MACHINE OR THE LIKE

## (57) Abstract

A method and a device in the drying section or the like of a paper machine or the like, in which a web (16) being conveyed from the opening nip ( $K_1$ ) between a cylinder (10) and a supporting fabric (18) toward a roll (14), is supported by a negative pressure created by a blow box (30) or the like. The negative pressure in the so called intensified negative pressure region (34'), i.e. close to the disengaging point (40) between the supporting fabric and the cylinder, is greater than at a distance from this disengaging point. According to the invention the negative pressure is controlled in the intensified negative pressure region (34') according to one or more parameters which act on the runability of the web and which can be varied or which vary during the run, such as the velocity of the web, the solid contents of the web, the composition of the pulp which is used, the paper or paper board quality which is produced, the grammage of the web, a characteristic of the web, such as the porosity, the traction acting in the web, or the web tension, the cylinder temperature, and/or the running situation, such as a web break, a threading situation, or a normal run, so that the desired runability is maintained between the cylinder (10) and the roll (14).

